



Product Code: BTJ2550TA

Air Hydraulic

Truck Jack

2-Stage 25,000kg 50,000kg

The BTJ2550TA quickly and easily manages a hefty 50,000kg in the first stage lift position and 25,000kg at the higher 2nd stage extension. This Air Actuated Commercial Jack is designed for heavy duty commercial use and features a long reach "T" handle and large rubber wheels for smooth manoeuvring around the workshop. With a minimum height of 215mm this jack is ideal for medium ground-clearance vehicles and a high lift maximum of 564mm (includes additional lifting saddles), this BORUM Air Actuated Jack is a very versatile heavy-lifter suitable for most workshops.



Features

Seals made in America

Double Sealing Function using XTP Industry Sealing Telescopic air actuation lift (air-hydraulic pump)
Long T-handle easily positions jack under vehicle Self-Returning Lowering and Lifting Switch Internal and External Cylinders hard chromed High manoeuvrability & deep reach under vehicles 2 extension adaptors / saddle plates
Large rubber wheels

All adaptors can be properly stored for transport on each side of the jack

INDUSTRIAL QUALITY

Specifications

First Stage: 50,000kg Safe Working Capacity Second Stage: 25,000kg Safe Working Capacity

First Stage Hydraulic Lift: 115mm Second Stage Hydraulic Lift: 114mm

Minimum Height: 215mm Maximum Height: 564mm Adaptors: 45mm and 75mm Handle Length: 1380mm

Operating Air Pressure: 145-175psi

Chassis: 805x282x215mm

Nett Weight: 73kg

Superior Quality since

1984

more than 30 years serving Australia's trade